

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
5 July 2001 (05.07.2001)


(10) International Publication Number
WO 01/48784 A1

PCT

- (51) International Patent Classification⁷: H01J 29/07
- (21) International Application Number: PCT/EP00/13362
- (22) International Filing Date:
22 December 2000 (22.12.2000)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data:
99204546.8 24 December 1999 (24.12.1999) EP
- (71) Applicant (for all designated States except US): KONINKLIJKE PHILIPS ELECTRONICS N.V. (NL/NL); Groenewoudseweg 1, NL-5621 BA Eindhoven (NL).
- (72) Inventor; and
(75) Inventor/Applicant (for US only): VAN DER WILK,
- Ronald (NL/NL); Prof. Holstlaan 6, NL-5656 AA Eindhoven (NL).
- (74) Agent: BAELE, Ingrid, A., F., M.; Internationaal Octrooibureau B.V., Prof Holstlaan 6, NL-5656 AA Eindhoven (NL).
- (81) Designated States (national): CN, JP, KR, US.
- (84) Designated States (regional): European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, TR).
- Published:**
- With international search report.
 - Before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments.
- For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.*

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: A COLOR CATHODE RAY TUBE COMPRISING A TENSION MASK



(57) Abstract: A cathode ray tube comprises a color selection electrode with a shadow mask fixed to a frame and put under tension. The frame comprises a bimetal element (or bimetal elements) which are constructed such that at a raised temperature the tension is released by reducing the distance between sides of the frame to which the mask is attached. The reduction in distance at the center of the sides exceeds, preferably by a factor 1.5 to 3, the reduction in distance at the corners of said sides.